








Offshore® 105

	OFFSHORE 105
Boat size	Powerboats of 5 to 9 m (17 to 30 ft).
Compass card	Graduated every 5°, apparent Ø 91 mm. Heading numerals every 30°.
Hood/sunshade	Articulated protective hood : built-in sliding cover, composed of 3 telescopic parts.
Mounting	Comes as standard in a flushmount version. Can be bracket-mounted with the addition of optional bracket.
Resistance to vibrations and hull pounding	Magnetic cell mounted on shock absorbers.
Lubber line	1 lubber line.
Compensation	Supplied as standard.
Lighting	On flat card : 2 bulbs, 12 V.On conical card : 1 bulb, 12 V.
Approval/homologation	ISO 613 compliant.

OFFSHORE 105

• BLACK COMP



OFFSHORE 105	Flushmount	Optional bracket kit*
BLACK COMPASS		
black flat card	17263	17268*
black conical card	17264	17268*
WHITE COMPASS		
black flat card	17265	17267*
black conical card	17266	17267*
white conical card	48972	17267*


^{*}The bracket kit includes the actual bracket and the adequate screws. A bracket-mount compass consists in one flushmount compass, plus one bracket kit (indicate both references when ordering).



Built-in articulated hood: slide it gradually on the compass to adapt to the light and avoid glare on the dome. When totally shut, your compass is perfectly protected.

The optional bracket brings additional mounting possibilities, either on a horizontal surface avoiding to cut the instrument panel or on a vertical bulkhead. The bracket slides onto a fixing plate, allowing easy removal after use for complete security from theft. Beyond a simple aesthetic preference, the bracket mounting also offers the extra advantage of isolating the compass from the dashboard, thus reducing the potential interference created by other instruments and metallic objects.

	OFFSHORE 135
Boat size	Powerboats of 10 m and above (33 ft +).
Compass card	Graduated every 5°, apparent Ø 130 mm. Heading numerals every 30°.
Hood / sunshade	Articulated protective hood: built-in sliding cover, composed of 3 telescopic parts.
Mounting	Comes as standard in a flushmount version. Can be bracket-mounted with the addition of optional bracket.
Resistance to vibrations and hull pounding	Magnetic cell mounted on shock absorbers.
Lubber line	1 lubber line.
Compensation	Supplied as standard.
Lighting	On flat card : 2 bulbs, 12 V.On conical card : 1 bulb, 12 V.
Homologation	SOLAS-MED 96/98
Homologation	SOLAS-MED 96/98



Flushmount	Optional bracket kit*
17259	17260*
23484	17260*
17261	17262*
23493	17262*
	17259 23484 17261

*The bracket kit includes the actual bracket and the adequate screws. A bracket-mount compass consists in one flushmount compass, plus one bracket kit (indicate both references when ordering).