



# Offshore® 95



6-10m



## Offshore® 95

	OFFSHORE 95
Boat size	Powerboats from 6 to 10 m (19 to 33 ft)
Compass card	Conical or flat card graduated every 5°, apparent Ø 81 mm. Heading numerals every 30°.
Mounting	<ul style="list-style-type: none"><li>• Flushmount, on a horizontal surface.</li><li>• With a bracket : mounted on a horizontal or inclined surface. Compass is removable thanks to clip-plate.</li></ul>
Resistance to vibrations and hull pounding	Magnetic cell equipped with the unique "Vibration Absorber" system.
Lubber line	1 lubber line.
Compensation	Supplied as standard.
Lighting	1 bulb 12 V, included.
Supplied with	Clip-plate, screws, drilling template.
Homologation	ISO 613 compliant.

OFFSHORE 95	flushmount	bracket
• BLACK COMPASS		
black flat card	55370	55376
black conical card	55373	55379
• WHITE COMPASS		
black flat card	55382	55391
black conical card	55385	55394
white conical card	55388	55397







### Card

Outstanding legibility under all weather and light conditions for optimum comfort and accurate readings.

- Perfect stability of conical or flat card, 81 mm apparent diameter.
- Every card is balanced individually in our workshops.
- Graduation every 5°.

### Lubber line

Orange, for instant recognition.



### Watertight construction

- One-piece moulded flange and bowl.
- Viton® diaphragm with extreme expansion and retraction capacity : compensates the fluctuations in fluid volume caused by differences in temperature and atmospheric pressure, preventing the formation of bubbles.
- Moulded-in sunken head screws.

### Materials

- All parts fully UV-ray treated.
- Scratch resistant dome.

### Lighting

Bulb is integrated in the bowl, thus spreading the illumination evenly and preventing eye strain and fatigue at night.

### Access to compensation or lighting

- Extremely easy access to compensation or lighting with unique flange-clip system.
- Compensation can be adjusted from the outside, with no need to open the compass on the bracket version.



### Installation

- **Flushmount on horizontal surface :** compact design, interchangeable with Offshore 90 and most compasses of equivalent size.
- **Bracket :** broad and sturdy bracket base absorbing vibrations. Mounting can be done whatever the angle, provided that the compass and card unit remain horizontal at all times. Bracket-mount compass can also be removed when fitted with clip-plate.



Optimum vibration-resistance for a perfect stability of the card. "Vibration Absorber" exclusive system : minimal contact between the pivot and the sapphire cup.

### Options

- **Protective cover :**  
white : 55402  
black: 55599



- **Plasticlip : 37035**

